

Product Technical Data Sheet

8155T – Silicone Spray

Summary

A suitably formulated silicone spray, that when applied to machine parts will act as a lubricant, reducing friction between surfaces, and increasing the lifespan of these parts. Can be used on most surfaces to act as a repellent to various materials such as water, ink, grease, as well as allowing paper to feed and “slip” off surfaces more easily whilst adding anti-corrosion properties.

Properties

Flashpoint (°C)	<-40C
Colour	N/A
State	Aerosol
Volume	400ml
Voc Content / % Volume	100%
Odour	Characteristic
UN Number	1950

Description of use

Apply by directly spraying onto selected products.

Storage, Shelf Life and Health and Safety

- Store in temperatures not exceeding 30°C and not falling below 5°C!
- Store on either pallets or racking in order to protect from cold floors.
- If left unopened and kept in the correct conditions this product has a recommended shelf life of 12 months.

Labeling: GHS02: Flame
GHS07: Exclamation
GHS09: Environmental

Usage: Will not give rise to any significant hazard provided reasonable standards of industrial practice are maintained.

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

Total Graphic Supplies Ltd

Unit 7c Petre Court
Petre Road
Accrington
Lancashire
BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: info@totalgraphics.co.uk
Web: www.totalgraphics.co.uk