

MULTI SEAL HARD DRY

Hard Drying Satin/Neutral Sheetfed Sealer

High solids, vegetable based, hard drying satin/neutral (pigmented) sheetfed sealer that has been specifically designed for overprinting and sealing printed papers and boards. It is particularly effective in preventing marking and scuffing during cutting, creasing and bindery operations and is recommended as a problem solving sealer.

Formulated with the use of new high molecular weight resin technology, this product possesses good body but superior flow properties, which are critical in this specific application area.

Ideally suited for fast work and turn+printing due to its fast drying and excellent rub and scuff resistance properties.

This product is quick setting, exhibits good lithographic and press stability and dries rapidly to produce a non-yellowing satin finish on the printed substrate.

Recommended for use when printing jobs that need to be backed up or finished quickly.

Product Specification

Viscosity (falling bar @ 25°C)	PV 50 . 60 poises YV 3000 . 4000 dynes/sq cm
Viscosity Under Sheer (Bohlin @ 25°C)	108 Pa: 28 . 34 4700 Pa: 18 - 23
Tack (Tack-O-scope 0.30ml/150m/s)	75 . 90
Drying time at room temperature (38 micron on glass)	6 . 8 hours vs standard

The information contained in this data sheet is derived from analysis from a typical sample. It is given for guidance purposes only, without guarantee.

Total Graphic Supplies Ltd
Unit 7c Petre Court
Petre Road
Accrington
Lancashire
BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: info@totalgraphics.co.uk
Web: www.totalgraphics.co.uk