

## Multi Seal

### Low Tack Neutral Sheetfed Sealer

Low tack Neutral sheetfed sealer that has been specifically designed for overprinting and sealing printed papers and boards.

Formulated with the use of new high molecular weight resin technology, this product possesses good body but superior flow properties, which are critical in this specific application area.

Ideally suited for use on perfector presses due to its excellent machine and lithographic stability.

This product will not skin in the duct if left overnight under normal conditions and dries to give a satin finish on the printed substrate.

A quick setting sealer that exhibits very good rub resistance and with superior non-yellowing properties on the final print.

Recommended for use where UV varnishing and additional print finishing has been specified.

### Product Specification

Viscosity (falling bar @ 25°C)	PV 50 . 60 poises YV 3000 . 4000 dunes/sq cm
Tack (Tack-O-scope 0.30ml/150m/s)	75 . 90
Viscosity Under Sheer (Bohlin @ 25°C)	108 Pa: 28 - 34 4700 Pa: 18 - 23
Drying time (38 micron on glass @ 32°C)	6 . 8 hours vs standard

**Total Graphic Supplies Ltd**

Unit 7c Petre Court  
Petre Road  
Accrington  
Lancashire  
BB5 5HY

Office: 01254 879 352

Fax: 01254 385 306

Email: [info@totalgraphics.co.uk](mailto:info@totalgraphics.co.uk)

Web: [www.totalgraphics.co.uk](http://www.totalgraphics.co.uk)